

SE5N60
5A,600V N-Channel MOSFET

Revision:A

General Description


The MOSFETs from SINO-IC provide the best combination of fast switching, low on-resistance and cost-effectiveness.

Features

- V_{DS} (V) = 700V @150°C
- I_D = 5A
- $R_{DS(ON)} < 1.8 \Omega$ ($V_{GS} = 10V$)

Pin configurations

See Diagram below



Absolute Maximum Ratings

Parameter		Symbol	Rating	Units
Drain-Source Voltage		V_{DS}	600	V
Gate-Source Voltage		V_{GS}	±30	V
Drain Current (Note 1)	Continuous	I_D	5	A
	Pulsed		16	
Total Power Dissipation		P_D	132	W
Operating Junction Temperature Range		T_J	-50 to 150	°C

Thermal Characteristics

Parameter		Symbol	Typ	Max	Units
Maximum Junction-to-Ambient A	$t \leq 10s$	$R_{\theta JA}$	54	65	°C/W
Maximum Case-to-Sink	Steady-State	$R_{\theta CS}$	-	0.5	°C/W
Maximum Junction-to-- Case	Steady-State	$R_{\theta JC}$	0.76	0.95	°C/W

SE5N60

Electrical Characteristics (T _J =25°C unless otherwise noted)						
Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
OFF/ON CHARACTERISTICS (Note 2)						
BV _{DSS}	Drain-Source Breakdown Voltage	I _D =250 μ A, V _{GS} =0 V	600			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =600 V, V _{GS} =0 V			1	μ A
I _{GSS}	Gate-Body leakage current	V _{DS} =0 V, V _{GS} =±30 V			±100	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} I _D =250 μ A	3	3.9	5	V
R _{DS(ON)}	Static Drain-Source On-Resistance ²	V _{GS} =10V, I _D =2.5 A	-	1.44	1.8	Ω
g _{FS}	Forward Transconductance	V _{DS} =40V, I _D =2.5A	-	7.7	-	S
DYNAMIC PARAMETERS						
C _{iss}	Input Capacitance	V _{GS} =0V, V _{DS} =25V, f=1MHz	466	583	700	pF
C _{oss}	Output Capacitance		46	58.4	70	pF
C _{rss}	Reverse Transfer Capacitance		4.2	5.3	6.5	pF
t _{ON}	Turn-On Time	V _{DS} =300V, I _D = 5A, V _{GS} = 10 V, R _{GEN} =25 Ω	-	21	25	ns
t _{OFF}	Turn-Off Time		-	35	45	ns
T _r	Turn-on Rise Time		-	44	55	ns
T _f	Turn-on Fall Time		-	37	45	ns
Q _{g(10)}	Total Gate Charge	V _{DS} =480V, I _D =2A, V _{GS} =10V	-	16.8	20	nC
Q _{gs}	Gate-Source Charge		-	3.1	4	nC
Q _{gd}	Gate-Drain Charge		-	8.5	11	nC
t _{rr}	Body Diode Reverse Recovery Time	I _F =5A, dI/dt=100A/ μ s	-	208	250	ns
Q _{rr}	Body Diode Reverse Recovery Charge	I _F =5A, dI/dt=100A/ μ s	-	2	2.4	uc

Typical Characteristics




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: Break Down vs. Junction Temperature




Figure 6: Body-Diode Characteristics




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating




Figure 10: Current De-rating (Note B)




Figure 11: Normalized Maximum Transient Thermal Impedance (Note F)

The SINO-IC logo is a registered trademark of ShangHai Sino-IC Microelectronics Co., Ltd.

© 2005 SINO-IC – Printed in China – All rights reserved.

SHANGHAI SINO-IC MICROELECTRONICS CO., LTD

Add: Building 3, Room 3401-03, No.200 Zhangheng Road, ZhangJiang Hi-Tech Park, Pudong,
Shanghai 201203, China

Phone: +86-21-33932402 33932403 33932405 33933508 33933608

Fax: +86-21-33932401

Email: webmaster@sino-ic.com

Website: <http://www.sino-ic.com>